

1. Identification

Product identifier **SDA 38B-17 200 Proof**
Other means of identification None.
Recommended use General purpose solvent.
Recommended restrictions Use in accordance with supplier's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company Name Greenfield Global USA Inc.
Address 1101 Isaac Shelby Drive
 Shelbyville, KY 40065
 USA
Telephone 502.232.7600
Fax 502.633.6100

Company Name Greenfield Global USA Inc.
Address 58 Vale Road
 Brookfield, CT 06804
 USA
Telephone 203.740.3471
Fax 203.740.3481

Emergency phone number
USA CHEMTREC: 1.800.424.9300 (CCN 17213)
International CHEMTREC: +1.703.527.3887 (CCN 17213)

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2
Health hazards Serious eye damage/eye irritation Category 2
 Sensitization, skin Category 1
OSHA defined hazards Not classified.

Label elements



Signal word Danger
Hazard statement Highly flammable liquid and vapor. Causes serious eye irritation. May cause an allergic skin reaction.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapor. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage	Store in a well-ventilated place. Keep cool.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Ethyl alcohol	64-17-5	91 - < 99
Peppermint Oil	8006-90-4	1 - < 2
Water	7732-18-5	0 - < 8

Composition comments All concentrations are in percent by weight unless otherwise indicated.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
General information	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed. Combustion products may include: carbon oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to keep fire-exposed containers cool.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. The product is completely soluble in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions**7. Handling and storage****Precautions for safe handling**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Ethyl alcohol (CAS 64-17-5)	PEL	1900 mg/m ³
		1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ethyl alcohol (CAS 64-17-5)	TWA	1900 mg/m ³
		1000 ppm

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Chemical goggles are recommended.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Skin protection**Other**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Respirator type: Chemical respirator with organic vapor cartridge.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties**Appearance**

Physical state	Liquid.
Form	Liquid.
Color	Clear liquid; invisible vapor.

Odor Characteristic.

Odor threshold Not available.

pH Not available.

Melting point/freezing point -173.38 °F (-114.1 °C)

Initial boiling point and boiling range 173.3 °F (78.5 °C)

Flash point 57.2 °F (14.0 °C) closed cup

Evaporation rate 3.3 (butyl acetate = 1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 3.3 % v/v (for 100% Ethyl alcohol)

Flammability limit - upper (%) 19 % v/v (for 100% Ethyl alcohol)

Vapor pressure 44.6 mm Hg (5.94 kPa) (68 °F (20 °C))

Vapor density 1.6 (air = 1)

Relative density 0.789 (68 °F (20 °C))

Solubility(ies)

Solubility (water) Completely soluble.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature 685.4 °F (363 °C) (Ethyl Alcohol)

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure**

Inhalation Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction. Causes mild skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Ethyl alcohol (CAS 64-17-5)		
Acute		
Inhalation		
<i>Vapor</i>		
LC50	Rat	117 - 125 mg/l, 4 Hours
Oral		
LD50	Rat	10470 mg/kg

Skin corrosion/irritation Causes mild skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Ethyl alcohol (CAS 64-17-5)		
Aquatic		
Algae	EC10	Freshwater algae 11.5 mg/l, 72 hours
	EC50	Freshwater algae 275 mg/l, 72 hours
		Marine water algae 1900 mg/l
	NOEC	Marine water algae 1580 mg/l
Fish	LC50	Freshwater fish 11200 mg/l, 24 hours
	NOEC	Freshwater fish 250 mg/l
Invertebrate	EC50	Freshwater invertebrate 5012 mg/l, 48 hours
		Marine water invertebrate 857 mg/l, 48 hours
	NOEC	Freshwater invertebrate 9.6 mg/l, 10 days

Components		Species	Test Results
		Marine water invertebrate	79 mg/l, 96 hours
Other	EC50	Lemna minor	4432 mg/l, 7 days
	NOEC	Lemna minor	280 mg/l, 7 days
Other			
Micro-organisms	LC50	Micro-organisms	5800 mg/l, 4 hours
Terrestrial			
Plant	EC50	Terrestrial plant	633 mg/kg dw

Persistence and degradability	There are no data on the degradability of this product.
Bioaccumulative potential	No data available for this product.
Mobility in soil	The product is completely soluble in water.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number	UN1170
UN proper shipping name	Ethyl alcohol solution
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	24, IB2, T4, TP1
Packaging exceptions	4b, 150
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1170
UN proper shipping name	Ethyl alcohol solution
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	No.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1170
UN proper shipping name	ETHYL ALCOHOL SOLUTION

Transport hazard class(es)**Class** 3**Subsidiary risk** -**Packing group** II**Environmental hazards****Marine pollutant** No.**EmS** F-E, S-D**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not established.**15. Regulatory information****US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Not listed.

SARA 311/312 Hazardous chemical Yes**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)
Serious eye damage or eye irritation
Respiratory or skin sensitization**SARA 313 (TRI reporting)**

Not regulated.

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

Ethyl alcohol (CAS 64-17-5)

Low priority

US state regulations**US. Massachusetts RTK - Substance List**

Ethyl alcohol (CAS 64-17-5)

US. New Jersey Worker and Community Right-to-Know Act

Ethyl alcohol (CAS 64-17-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethyl alcohol (CAS 64-17-5)

US. Rhode Island RTK

Ethyl alcohol (CAS 64-17-5)

California Proposition 65California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 26-September-2018

Revision date -

Version # 01

HMIS® ratings
Health: 2
Flammability: 3
Physical hazard: 0

Disclaimer This product is subject to Greenfield Global USA Inc.'s terms and conditions, which can be found at <http://www.greenfield.com/tc-po-us/>. Greenfield cannot anticipate all conditions under which this information and this product, or the products of other manufacturers in combination with this product, may be used. The user is responsible for the proper and safe use, handling, storage and disposal of the product, and assumes liability for any loss, injury, damage or expense arising from any failure to do so. The data in this sheet is based on information and experience available at the time of writing.